



COATING STRIPPER

Description

A powerful, professional strength, ready-to-use stripper formulated specifically for removing tough coatings from natural stone, tile, and concrete surfaces. Safely and effectively dissolves a wide range of topical coatings, including epoxy and urethane grout haze, paint, and adhesives. The right choice for cleaning professionals, restoration contractors, and ambitious DIYers.

Features

- Safe for Natural Stone, Ceramic, Porcelain, and Concrete
- Water Based
- Removes Epoxy and Urethane Grout Haze, Paint & Adhesives
- VOC Compliant
- Degrades Penetrating Sealers
- Professional Grade

Recommended Surface Types

Natural stone, including granite, slate, limestone, sandstone, bluestone, concrete, Saltillo and other clay-based tile. Ceramic and porcelain.

Coverage

400 sq. ft. per Gallon

pH Measurement

6.0

Available Sizes

Quart, Gallon

Emergency / First Aid Procedures

IF INHALED: Get medical advice/attention if you feel unwell.
IF ON SKIN: Wash with plenty of soap and water. If irritation (redness, rash, blistering) develops, get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

EMERGENCY HOT LINE: 800-222-1222

Contact Information

MORE™ Surface Care, LLC
Palo Alto, California, USA
844-404-MORE (6673)
www.moresurfacecare.com

Storage and Handling

Keep out of reach of pets and children. Avoid contact with skin and eyes. Minimize exposure to vapors. Wear protective gloves/eye protection. Store and use in a well ventilated area. Dispose of unused product in accordance with local laws and guidelines. DO NOT allow to freeze. DO NOT mix with other chemicals.

Usage Instructions:

1. Read entire label before using and use only as directed.
2. Sweep or vacuum loose debris and dirt from surface.
3. Protect surrounding surfaces by masking off areas not intended to be stripped.
4. Always test product in an inconspicuous area to ensure desired results.
5. Keep work area well ventilated during application.
6. Apply a liberal amount of coating stripper with a paint brush or paint pad and allow to dwell on the surface for 60 minutes.
7. Scrub surface with a brush or other appropriate cleaning tools.
8. Remove solution using a mop or wet / dry vacuum.
9. Multiple applications may be required. Repeat steps 6 – 8 as needed.
10. Rinse thoroughly with clean water and allow surface to dry completely before resuming use.
11. For ongoing stain protection seal surface with MORE™ Premium Natural stone Sealer.
12. Use MORE™ Stone and Tile Cleaner to maintain your surface every day.

Satisfaction Guarantee

MORE™ Surface Care, LLC warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. MORE™ Surface Care's sole liability under this warranty shall be limited to replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with MORE™ Surface Care's printed instructions. MORE™ SURFACE CARE MAKES NO OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country and / or territory to another. This warranty is not transferrable.